

PRODUCT VISUAL



PRODUCT DESCRIPTION

Digital terrestrial receiver, with 320 GB PVR. **Especially made for Boxer**

Especially made for use in Sweden.

Boxer Sweden approved.

Not for use in Denmark !!!

FEATURES

- Powerful combination of IBM PowerPC hardware and firmware based on Linux O/S
- **2-Tuner PVR Digital Terrestrial Receiver**
- **Viaccess embedded and 2 common interface**
- JPEG-mode: picture viewer and slide show generator and MP3 player
- **Dual Recording and Playback simultaneously**
- **Dual Recording and Time-shifting simultaneously**
- **Recorded files are fully editable**
- Software PIP (Picture-In-Picture)
- Powerful trick mode
- **Boxer navigator EPG function**
- Dot Matrix Vacuum Fluorescent Display
- True Color OSD (On-Screen-Display)
- Supports enhanced EPG with the PVR features
- DVB and Teletext subtitles available, Teletext Page memory up to 10000 pages
- 10/100 Mbps TCP/IP Ethernet
- Real Time Clock embedded
- S/PDIF output for digital audio or Dolby AC-3 bitstream output

TECHNICAL SPECIFICATIONS

Conditional Access Interface

Embedded crypt.: Conax
PCMCIA: 2 x CI slot(s)

Tuner & Channel

Input connector: RF 75 Ω IEC 169-24, 2 inputs
Output connector: RF 75 Ω IEC 169-24, 2 outputs
Input frequency range: VHF: 174 ~ 230 MHz; UHF: 470 ~ 862 MHz
Signal level: -65 to -25 dBm

MPEG Transport Stream A/V Decoding

Transport stream: ISO/IEC 13818-2 MPEG-2
Profile level: MPEG-2 MP@ML
Aspect ratio: 4:3 / 16:9, Pan & Scan, Letterbox, Auto
Audio decoding: MPEG-1 Layer I, II & III
Video resolution: 720 x 576 (PAL)

Audio Output

SPDIF: Optical digital audio / Dolby AC-3 bitstream output

A/V Data In/Out

TV-Scart: Video CVBS/ Yc/ RGB/ YPbPr Output, Audio L/R Output
VCR-Scart: Video CVBS Output, Audio L/R Output Video, CVBS/ YC / RGB Input Bypass, Audio L/R Bypass
HDMI: HDMI 1.0 Uncompressed digital audio and video for the highest image quality
RCA A/V: Video CVBS Output, Audio L/R Output
Ethernet: 10/100 Mbit ethernet controller

Data In/Out

RS232C: data rate 115200 bps
USB: USB 2.0 Host controller

Processor and Memory

Processor: IMB power PC
System SDRAM: 48 MB
Flash memory: 8 MB
EEPROM: 2 KB
HDD: 320 GB

Power supply

Input voltage: 90 - 250 V AC, 50 / 60 Hz
Type: SMPS

Physical specification

Size (WxHxD): 380 x 60 x 300 mm

Front panel

Display: Dot-matrix VFD (Vacuum Fluorescent Display)

Rear panel

HDMI: HDMI output